

## Granville FS-G 5W/30

1 Litre, 5 Litre & 20 Litre

### PRODUCT DESCRIPTION

Granville FS-G 5W/30 is formulated primarily to meet the latest GM longlife requirements using the most advanced additive technology to produce a fuel efficient engine oil that has excellent high and low temperature performance and exceptional long term anti wear characteristics. Suitable for use in petrol & diesel engines where specified including: Vauxhall, Opel, Mercedes, BMW and Saab.

### RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: A3/B4

GM: LL-A-025 & LL-B-025

Opel: B-040-2095 & B-040-2098

MB: 229.3

BMW: LL-01 & LL-98

VW: 502.00 & 505.00

API: SL/CF



\* Image for illustrative purposes only.

| SIZE     | PART NO | BARCODE       |
|----------|---------|---------------|
| 1 Litre  | 2402    | 5020618024026 |
| 5 Litre  | 2403    | 5020618024033 |
| 20 Litre | 2408    | 5020618024088 |

### PRODUCT BENEFITS

- \* Ensures lubricant performance over extended drain intervals
- \* Excellent high & low temperature performance
- \* Outstanding fuel efficiency
- \* Effective environmental protection

### PRODUCT USAGE

For engines where this specification and viscosity of lubricant is required.

### DIRECTIONS FOR USE

As recommended by the engine manufacturer.



# Granville FS-G 5W/30

1 Litre, 5 Litre & 20 Litre

## STORAGE INSTRUCTIONS

Store upright and sealed in a cool, dry place out of the reach of children.

## SHELF LIFE

5 years from date of manufacture.

|                                |                      |
|--------------------------------|----------------------|
| <b>Appearance</b>              | : Amber liquid       |
| <b>Odour</b>                   | : Characteristic     |
| <b>Solubility</b>              | : Insoluble in water |
| <b>Percentage of Biodiesel</b> | : Nil                |

| Test                         | Method     | Unit               | Min. | Max.  | Typical |
|------------------------------|------------|--------------------|------|-------|---------|
| Kinematic Viscosity at 100°C | ASTM D445  | mm <sup>2</sup> /s | 9.3  | <12.5 |         |
| Cold Cranking Viscosity      | ASTM D4684 | mPa.s              |      | <6600 |         |
| Total Base Number            | ASTM D2896 | mg KOH/g           | 10   |       |         |
| HTHS Viscosity               | ASTM D4683 | mPa.s              | >3.5 |       |         |
| NOACK Volatility             | ASTM D5800 | %                  |      | 10    |         |
| Pour Point                   | ASTM D97   | °C                 |      | -27   |         |

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

